



## BPU 2540A US

### Reversible vibratory plate

Maximum compaction in the tightest spaces

The lightweight reversible vibratory plates are powerful and versatile making them ideal for base preparation, gardening, landscaping and maintenance work on streets, roads and parking lots. The Wacker Neuson vibratory plates in the 25-37 kN class come equipped with a sturdy, integrated wheel set. This unique feature provides mobility on the construction site. Due to their compact design and excellent maneuverability, the lightweight reversible vibratory plates are ideal for the compaction of trenches, sidewalks and other confined areas. Well thought-out design make them the ideal compaction machine for professional applications.

### Highlights

- Compact dimensions, high performance
- Integrated wheel set
- Sturdy and durable

### Technical Data

#### ■ Mechanical - Output Details

Centrifugal force	25 kN
Area capacity	456.0 m <sup>2</sup> /h
Forward Running	19.0 m/min
Gradeability	36.4 %
Vibrations (Hz)	90.0 Hz

#### ■ Mechanical Details

Length Baseplate	703.0 mm
Width	400.0 mm
Width Baseplate	400.0 mm
Height	1,097.0 mm
Height Cover frame	666.0 mm
Thickness Baseplate	10.0 mm

Operating weight	145.0 kg
Ground clearance	666.0 - 776.0 mm

#### ■ Engine

Effective power	3.1 KW
Nominal Engine speed	2,800.0 1/min

#### ■ Environment Data

HAV summation (average value)	m/s <sup>2</sup>
HAV summation (Standard)	EN 500-4

#### ■ Electrical System

Coding options	0
Remote Control Range	0.0 m

#### ■ Operating Fluids

Cooling fluid type	0
--------------------	---