





4-stroke Rammers

Excellent work performance and long service life

Wacker Neuson's four-stroke rammers are characterized by outstanding work performance. The large stroke, high ramming frequency, high impact energy and fast forward travel ensure first-class work results. Well thought-out functions also make the use of the four-stroke rammer even more user-friendly, extend its service life and reduce maintenance to a minimum.



Highlights

- Just one lever for starting, idling and stopping
- 4-stage air cleaner (cyclone, paper filter and 2 foam air cleaners)
- Honda engine
- Low oil warning indicator
- Fast travel speed

Technical Data

Number of blows

Mechanical - Output Details

Area capacity	119.0 m2/h
Forward Running	7.1 m/min
Power of impact	16.0 kN
Mechanical Details	
Length	673.0 mm
Length Ramming Shoe	340.0 mm
Width	343.0 mm
Width Ramming Shoe	280.0 mm
Height	940.0 mm
Weight	65.00 kg
Operating weight	65.0 kg
Stroke at tamper	61.0 mm

656.0 1/min

Engine

Fuel consumption	0.9 L/hr
Environment Data	
Operating temperature range	-10 - 40 °C
Sound power LWA, guaranteed	108.0 dB(A)
Sound power LWA (Standard)	EN 500-4
HAV summation (average value)	11.0 m/s2
HAV summation (Standard)	EN 500-4
Electrical System	
Display Equipment	Operating hours counter
Operating elements	Pushbutton OFF
Operating Fluids	
Oil specification	SAE 10W-40
Oil volume	0.700
Lubrication intervall	250.0 h

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.